TIME LED

SPECIFICATION SHEET

PRODUCT CODE: 783351

Powerful, slimline and lightweight, our range of LED panels is worth looking into. The panels bring you a range of innovative choices for commercial office lighting, retail and hospitality.

- Compatible with universal emergency modules
- Even distribution of flicker-free light
- Easy installation, no mounting kit required
- Simple retrofit directly onto T-bar ceiling grids
- Ultra-slim 9mm design
- · Lightweight 2kg
- Maintenance free

















707751







NON-DIMMABLE 30,000 HOURS LIFESPAN

UTILITY ULTRA PANEL -ECO - DAYLIGHT












SPECIFICATION

Product code	783351
Bulb Type	SMD
Wattage	40W
Equivalent wattage	400W
Lumens	3200lm
Driver included	Yes
Dimmable	No
Beam Angle	120°
Length	595mm²
Depth	9mm
Weight	2kg
Cut Out Size	575mm²
Cable Length	10cm
Lifespan	30,000 Hours
Warranty	5 Years
Energy consumption	40kWh/1000h
Energy rating	A+
Material	Aluminum & Iron
Packaging	Brown Box & Colour Sticker
IP Rating	IP20

Voltage	220-240V
Current	AC
Power	40W
ССТ	6000K
Ra	80
Lumens per watt	80lm/W
Colour tolerance	<6
Power factor	0.9
Input frequency	50Hz



220-240V



