TIME LED®

Utility 40W Frame LED Light Panel Non-Dimmable

Installation and Operating Instructions



Read and follow instructions before operating your light. Save this manual for future reference.

Package includes:

1 x Utility 40W Frame LED Light Panel Non-Dimmable

1 x Manual

Safety:

- This product must be installed in accordance with the latest edition of the IEE Wiring Regulations (BS7671) and current Building Regulations. If in any doubt, consult a qualified electrician.
- Isolate mains prior to installation or maintenance.
- Check the total load on the circuit (including when this luminaire is fitted) does not exceed the rating of the circuit cable, fuse or circuit breaker.
- This product is IP20 rated and suitable for interior installations only.
- The LEDs fitted in this product are non-replaceable.
- This product is non-dimmable.

INS-768976-768983-V2

TIME LED is part of Pitacs Limited. For customer support contact:

Bradbourne Point, Bradbourne Drive, Tilbrook, Milton Keynes, Buckinghamshire MK7 8AT

T: +44 (0)1908 271155 F: +44 (0)1908 640017 E: info@timeled.co.uk W: www.timeled.co.uk











Product Code	768976 68983
Size (mm)	591 x 591 x 10
Watts	40W
Lumens	3600lm
IP Rating	IP20
Beam Angle	120°

Instructions for new installations:



1) Ensure mains supply is switched off before installation.



3) Install the frame into the ceiling, ensuring to lay level and flat, replacing the ceiling board once in place.

Cleaning:

- Do not use any chemical or abrasive cleaners.
- Clean product with only a soft dry cloth.

Warning:

• This product must be disconnected from the circuit if subjected to any high voltage or insulation resistance testing. Irreparable damage will occur if this instruction is not followed.

Recycling Advice:

Waste Electrical products should not be disposed of with household waste. Please recycle where facilities exist. Check with your local authority or retailer for recycling advice.

Full Technical specification available upon request. Contact info@timeled.co.uk for PDF.



Net Weight	0.5kg
Lifespan	25,000 hours
Voltage	170-265V
Colour Temp	6000K Daylight (768983) 4500K Cool White (768976)
Energy Rating	A+
Warranty	3 Years



 Place connector, driver & cable into the ceiling void. Connect the power input line with the electricity supply and power output line with the frame.



4) Once the installation is complete, restore the electricity to the panel.

Utility 40W Frame LED Light Panel Non-Dimmable